

Printing date 26.10.2016 Version number 1 Revision: 26.10.2016

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: UV-Protection-Oil Tints

Article number: 424 Spruce, 425 Oak, 426 Larch, 427 Douglas, 428 Cedar, 429 Natural

1.2 Relevant identified uses of the substance or mixture and uses

advised against No further relevant information available.

Application of the substance / the

mixture Paint

Coating compound/ Surface coating/ paint

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier: Osmo Holz und Color GmbH & Co. KG

Affhüppen Esch 12 D-48231 Warendorf

Further information obtainable

from: Product safety department

Phone: +49 (0) 251 / 692 - 188 Fax: +49 (0) 251 / 692 - 462 e-mail: helmut.starp@osmo.de

1.4 Emergency telephone

number: emergency phone no. Berlin (24h): +49 (0) 30 / 30686 790 advisory service in German

and English

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

2.2 Label elements

Labelling according to Regulation

(EC) No 1272/2008 The product is classified and labelled according to the CLP regulation.

Hazard pictogramsVoidSignal wordVoid

Hazard statements H412 Harmful to aquatic life with long lasting effects.

Precautionary statements P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children. P273 Avoid release to the environment.

P501 Dispose of contents/container in accordance with local/regional/national/

international regulations.

Additional information: Observe the general safety regulations when handling chemicals.

Always wear a dust mask when sanding.

Contains propiconazole. May produce an allergic reaction.

Safety data sheet available on request.

(Contd. on page 2)



Printing date 26.10.2016 Version number 1 Revision: 26.10.2016

Trade name: UV-Protection-Oil Tints

(Contd. of page 1)

2.3 Other hazards

Results of PBT and vPvB assessment

PBT: Not applicable.*vPvB*: Not applicable.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Description: Mixture of substances listed below with nonhazardous additions.

Dangerous components:		
CAS: 64742-48-9	aliphatic hydrocarbons, C10-C13	20-<25%
918-481-9	♦ Asp. Tox. 1, H304	-
Index number: 649-327-00-6		
Reg.nr.: 01-2119457273-39		
CAS: 34590-94-8	(2-methoxymethylethoxy)propanol	10-<25%
EINECS: 252-104-2	substance with a Community workplace exposure limit	
Reg.nr.: 01-2119450011-60		
CAS: 127519-17-9	A mixture of branched and linear C7-C9 alkyl 3-[3-(2H-benzotriazol-2-yl)-5-	<3%
ELINCS: 407-000-3	(1,1-dimethyl-ethyl)-4-hydroxyphenyl]propionates	
Index number: 607-281-00-4	Aquatic Chronic 2, H411	
Reg.nr.: 01-0000015648-61		
CAS: 60207-90-1	propiconazole	<1%
EINECS: 262-104-4	Aquatic Acute 1, H400; Aquatic Chronic 1, H410; (1) Acute Tox. 4, H302;	=
Index number: 613-205-00-0	Skin Sens. 1, H317	

SECTION 4: First aid measures

Additional information:

4.1 Description of first aid measures

General information: Take affected persons out into the fresh air.

Immediately remove any clothing soiled by the product.

For the wording of the listed hazard phrases refer to section 16.

After inhalation: Supply fresh air; consult doctor in case of complaints.

After skin contact: Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.

After swallowing: Induce vomiting only, if affected person is fully conscious.

If swallowed, seek medical advice immediately and show this container or label.

4.2 Most important symptoms and

effects, both acute and delayed Headache

Dizziness

(Contd. on page 3)



Printing date 26.10.2016 Version number 1 Revision: 26.10.2016

Trade name: UV-Protection-Oil Tints

(Contd. of page 2)

4.3 Indication of any immediate medical attention and special

treatment needed No further relevant information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents: CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant

foam.

For safety reasons unsuitable

extinguishing agents: Water with full jet

5.2 Special hazards arising from

the substance or mixture Formation of toxic gases is possible during heating or in case of fire.

5.3 Advice for firefighters

Protective equipment: No special measures required.

Additional information Cool endangered receptacles with water spray.

Dispose of fire debris and contaminated fire fighting water in accordance with official

regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and

emergency procedures Ensure adequate ventilation

Keep away from ignition sources.

6.2 Environmental precautions: Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

6.3 Methods and material for

containment and cleaning up: Warm water and cleansing agent

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders).

6.4 Reference to other sections See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling Keep receptacles tightly sealed.

Use only in well ventilated areas.

Information about fire - and

explosion protection: No special measures required.

(Contd. on page 4)



Printing date 26.10.2016 Version number 1 Revision: 26.10.2016

Trade name: UV-Protection-Oil Tints

(Contd. of page 3)

7.2 Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by

storerooms and receptacles: Store only in the original receptacle.

Information about storage in one

common storage facility: Not required.

Further information about

storage conditions: Store receptacle in a well ventilated area.

Storage class: 10

7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

Additional information about

design of technical facilities: No further data; see item 7.

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

64742-48-9 aliphatic hydrocarbons, C10-C13

TWA (8 H) Long-term value: 1.000 mg/m³, 150 ppm ppm

Source: UK SIA

34590-94-8 (2-methoxymethylethoxy)propanol

WEL Long-term value: 308 mg/m³, 50 ppm

Sk

Additional information: The lists valid during the making were used as basis.

8.2 Exposure controls

Personal protective equipment: General protective and hygienic

measures: Do not eat, drink, smoke or sniff while working.

Do not carry product impregnated cleaning cloths in trouser pockets.

Avoid contact with the eyes and skin.

Respiratory protection: Use suitable respiratory protective device only when aerosol or mist is formed.

Not necessary if room is well-ventilated.

Short term filter device:

Gas filter EN 14387 Type A (organic gas / vapor (boiling point > 65 °C)).

Protection of hands: Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/

the preparation.

Selection of the glove material on consideration of the penetration times, rates of

diffusion and the degradation

Material of gloves The selection of the suitable gloves does not only depend on the material, but also on

further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be

(Contd. on page 5)



Printing date 26.10.2016 Version number 1 Revision: 26.10.2016

Trade name: UV-Protection-Oil Tints

(Contd. of page 4)

calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material The exact break trough time has to be found out by the manufacturer of the protective

gloves and has to be observed.

For the permanent contact gloves made of the following materials

are suitable: Nitrile rubber, NBR

As protection from splashes gloves made of the following

materials are suitable: Nitrile rubber, NBR

Eye protection: Goggles recommended during refilling

Body protection: Protective work clothing

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties			
General Information			
Appearance:			
Form:	Fluid		
Colour:	According to product specification		
Odour:	Mild		
Odour threshold:	Not determined.		
pH-value:	Not determined.		
Change in condition			
Melting point/Melting range:	Undetermined.		
Boiling point/Boiling range:	> 180 °C		
Flash point:	> 61 °C (DIN 53213)		
Flammability (solid, gaseous):	Not applicable.		
Ignition temperature:	Undetermined		
Decomposition temperature:	Not determined.		
Self-igniting:	Product is not selfigniting.		
Danger of explosion:	Product is not explosive. However, formation of explosive air/vapour mixtures a possible.		
Explosion limits:			
Lower:	0.7 Vol %		
Upper:	14.0 Vol %		
Vapour pressure at 20 °C:	0.4 hPa		
Density at 20 °C:	0.9-1.0 g/cm³ (DIN 51757)		

(Contd. on page 6)



Printing date 26.10.2016 Version number 1 Revision: 26.10.2016

Trade name: UV-Protection-Oil Tints

(Contd. of page 5)

Relative densityNot determined.Evaporation rateNot determined.

Solubility in / Miscibility with

water: Not miscible or difficult to mix.

Partition coefficient (n-octanol/water): Not determined.

Viscosity:

Dynamic: Not determined.

Kinematic at 20 °C: 60-80 s (DIN 53211/4 m)

Solvent content:

VOC (EC) < 400 g/l (VOC-max. Cat A/e (2010) = 400 g/l)

9.2 Other information No further relevant information available.

SECTION 10: Stability and reactivity

10.1 Reactivity No further relevant information available.

10.2 Chemical stability
Thermal decomposition /

conditions to be avoided: No decomposition if used and stored according to specifications.

10.3 Possibility of hazardous

reactions Reacts with fabric soaked in the product (e.g. cleaning wool).

10.4 Conditions to avoid No further relevant information available.10.5 Incompatible materials: No further relevant information available.

10.6 Hazardous decomposition

products: Carbon monoxide and carbon dioxide

Nitrogen oxides (NOx)

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification:
64742-48-9 aliphatic hydrocarbons, C10-C13

Oral	LD50	> 5000 mg/kg (rat) (OECD 401)
Dermal	LD50	> 5000 mg/kg (rat) (OECD 402)
Inhalative	LC50 / 4h	21 mg/l (rat) (OECD 403)

127519-17-9 A mixture of branched and linear C7-C9 alkyl 3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethyl-ethyl)-4-hydroxyphenyl]propionates

Inhalative LC50 / 4h >5 mg/l (rat)

(Contd. on page 7)



Printing date 26.10.2016 Version number 1 Revision: 26.10.2016

Trade name: UV-Protection-Oil Tints

(Contd. of page 6)

Primary irritant effect:

Skin corrosion/irritation At long or repeated contact with skin it may cause dermatitis due to the degreasing

effect of the solvent.

Serious eye damage/irritationBased on available data, the classification criteria are not met.Respiratory or skin sensitisationBased on available data, the classification criteria are not met.SensitisationContains propiconazole. May produce an allergic reaction.

CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)

Germ cell mutagenicityBased on available data, the classification criteria are not met.CarcinogenicityBased on available data, the classification criteria are not met.Reproductive toxicityBased on available data, the classification criteria are not met.STOT-single exposureBased on available data, the classification criteria are not met.STOT-repeated exposureBased on available data, the classification criteria are not met.Aspiration hazardBased on available data, the classification criteria are not met.

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity:			
127519-17-9 A mixture of branched and linear C7-C9 alkyl 3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethyl-ethyl)-4-			
hyo	hydroxyphenyl]propionates		
EC50 / 48h	3.2 mg/l mg/l (daphnia) (OECD-Richtlinie 202, Teil 1)		
BiokonzFaktor	<3 (OECD-Richtlinie 305 C)		
60207 00 1 ppor	-i		

60207-90-1 propiconazole

EC50 / 48h	10.2 mg/l (daphnia) (202 Daphnia sp. acute Immobilization)
EC50/ 72h	9 mg/l (algae) (201 Alga Growth, Inhibition Test (Biomasse))
LC50 / 96h	4.3 mg/l (fish) (203 Fish Acute Toxicity)
LC50 / 48h	10.2 mg/l (fish)

12.2 Persistence and degradability No further relevant information available.
12.3 Bioaccumulative potential No further relevant information available.
12.4 Mobility in soil No further relevant information available.

Ecotoxical effects:

Remark: Harmful to fish

Additional ecological information:

General notes: Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Danger to drinking water if even small quantities leak into the ground.

Harmful to aquatic organisms

12.5 Results of PBT and vPvB assessment

PBT:Not applicable.vPvB:Not applicable.

(Contd. on page 8)



Printing date 26.10.2016 Version number 1 Revision: 26.10.2016

Trade name: UV-Protection-Oil Tints

(Contd. of page 7)

12.6 Other adverse effects

No further relevant information available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Recommendation Must not be disposed together with household garbage. Do not allow product to reach

sewage system.

European waste catalogue

08 01 11* waste paint and varnish containing organic solvents or other dangerous substances

15 01 10* packaging containing residues of or contaminated by dangerous substances

Uncleaned packaging:

Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information

14.1 UN-Number ADR, ADN, IMDG, IATA	Void	
14.2 UN proper shipping name	V-: J	
ADR, ADN, IMDG, IATA	Void	
14.3 Transport hazard class(es)		
ADR, ADN, IMDG, IATA		
Class	Void	
14.4 Packing group		
ADR, IMDG, IATA	Void	
14.5 Environmental hazards:		
Marine pollutant:	No	
14.6 Special precautions for user	Not applicable.	
14.7 Transport in bulk according to Annex II of Marpol		
and the IBC Code	Not applicable.	
UN "Model Regulation":	Void	

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REGULATION (EC) No

1907/2006 ANNEX XVII Conditions of restriction: 3, 55

(Contd. on page 9)



Printing date 26.10.2016 Version number 1 Revision: 26.10.2016

Trade name: UV-Protection-Oil Tints

(Contd. of page 8)

National regulations:

VOC(EC) < 400 g/l (VOC-max. Cat A/e (2010) = 400 g/l)

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H317 May cause an allergic skin reaction.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects. H411 Toxic to aquatic life with long lasting effects.

Department issuing SDS: product safety department

Contact: Hr. Dr. Starp

Abbreviations and acronyms: ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement

concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Acute Tox. 4: Acute toxicity – Category 4 Skin Sens. 1: Skin sensitisation – Category 1 Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2

 $Aquatic\ Chronic\ 3:\ Hazardous\ to\ the\ aquatic\ environment\ -\ long-term\ aquatic\ hazard\ -\ Category\ 3$

GB